

PORST 02/19/85
11-3.125.1v1
BOK 10

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME Borden Inc., Krylon Department		EMERGENCY TELEPHONE NO. (215) 278-2400 or 278-2456
ADDRESS (Number, Street, City, State, and ZIP Code) Ford & Washington Sts., Norristown, PA 19404.		
CHEMICAL NAME AND SYNONYMS n.a.	TRADE NAME AND SYNONYMS [REDACTED]	
CHEMICAL FAMILY n.a.	[REDACTED]	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV ppm	CAS Number
PIGMENTS			
Vary with color	0.5 to 8.6	Not toxic or hazardous	
VEHICLE			
Film-forming resins & plasticizers	9 to 12	Not toxic or hazardous	
SOLVENTS			
Acetone	37	750	67 64 1
Propane	16.5	E	74 98 6
Methyl isobutyl ketone	7 to 15	50	108 10 1
Methyl ethyl ketone	2 to 9	200	78 93 3
Toluene	2 to 12	100	108 88 3
Xylene	0 to 6	100	1330 20 7
2-Ethoxyethyl acetate	3 to 5	5	111 15 9
Butyl alcohol	1 to 3	C50	71 36 3

Note: E = Simple Asphyxiants, C = Ceiling limit

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	n.a.	SPECIFIC GRAVITY (H ₂ O=1)	< 1
VAPOR PRESSURE (mm Hg.)	n.a.	PERCENT. VOLATILE BY VOLUME (%)	80 - 90
VAPOR DENSITY (AIR=1)	> 1	EVAPORATION RATE butyl acetate = 1	> 1
SOLUBILITY IN WATER	Slight	Container is under internal pressure of about 60 pounds per square inch gauge	
APPEARANCE AND ODOR	n.a.	at 70°F.	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point n.a. - Product classified (Extremely) Flammable per 16CFR1500.3(c)(6); & 49CFR173.300.

If sprayed directly at a nearby open flame, spray may catch fire and burn like a blowtorch.
(This is not dangerous to the unit; release spray button to extinguish flame.)

If the spray mist or the vapors evaporating from a deposited film collect in a confined or closed area or in a pit or depression or box, and if the concentration is 1.5 grams or more of can content per cubic foot of air (content of one can or more per 250 cubic feet of air), it may have reached the lower explosive limit and could be ignited by a flame or spark.

If can is in a fire it may burst (with violence) due to the heat, and this will release its flammable content.

These would be solvent fires -- Class B.

USEPA SF
1265504

BOR 10

SECTION V - HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	Not applicable -- Mixture.
EFFECTS OF OVEREXPOSURE	Dizzy, confusion, weakness
EMERGENCY AND FIRST AID PROCEDURES	Get fresh air.
If sprayed in eyes, wash with water 15 minutes.	

SECTION VI - REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS Burning spray may produce toxic and irritating compounds.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	


SECTION VII - SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Remove sources of ignition.	
Soak up with absorbent material.	
Ventilate area.	
WASTE DISPOSAL METHOD When dry, discard as non-dangerous trash to be buried or burned.	

SECTION VIII - SPECIAL PROTECTION INFORMATION	
RESPIRATORY PROTECTION (Specify type)	Ventilate adequately.
VENTILATION Requirements vary with rate of product use. Supplement natural ventilation as necessary to keep area below threshold limit value of each ingredient. See Section II.	
PROTECTIVE GLOVES	Not needed
EYE PROTECTION	Desirable; not mandatory
OTHER PROTECTIVE EQUIPMENT	

SECTION IX - SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Do not store at temperatures over 120°F. Contents under pressure and exposure to high temperature may cause bursting. Avoid radiators, stoves, direct sunlight, or other heat source.	
OTHER PRECAUTIONS Incineration will cause container to burst violently. Avoid incineration or use only a strong, closed incinerator. Avoid puncturing as content will escape rapidly. If spray is burned do not breathe irritating or toxic fumes.	

PAGE (2)

Prepared by:



February 1, 1985

Form OSHA-20
Rev. May 72

DISCLAIMER

This data sheet is not part of any contract of sale; The information contained herein is believed to be correct or is obtained from sources believed to be generally reliable. However, it is the responsibility of the user of these materials to investigate, understand and comply with law and with procedures applicable to the safe handling and use of these materials.